



Product Name: **Polyglaze**
Reviewed Date: **January 2010**

Health & Safety Data Sheet Reference: **FT107**

1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Product name: **POLYGLAZE**

Supplier: Floortech Products
Goods Yard
Derby Road
Belper
Derbyshire
DE56 1UX

Phone: 01773 828111

Fax: 01773 828333

Product Description: Oil Modified Polyurethane

2- COMPOSITION/INFORMATION AND INGREDIENTS

Resin: 38-40% by weight.
Aliphatic/aromatic solvent blend: 60-62% by weight.

Name	EINICS No.	CAS No.	SI Number	Classification
White Spirit	265-191-7	64742-88-7	1300	R10,R51/53,R65,R66.
High Flash Aromatic	265-199-0	64742-95-6	1268	R10,R51/53,R65,R66.

3- HAZARD IDENTIFICATION

This product is classified as FLAMMABLE and HARMFUL under the current C.O.S.H.H. Regulations and the following risk and safety phrases must be applied:

R10: Flammable Liquid
R51/53: Toxic to aquatic organisms, may cause long-term
R65 - Harmful: May cause lung damage if swallowed.
R66 - Repeated exposure may cause skin dryness or cracking.

4- FIRST AID MEASURES

Eye Splashes: Flush the affected eye with clean running water for at least 15 minutes and seek medical advice.

Skin Exposure: Wash the affected area with clean soapy water for at least 10 minutes. If soreness or irritation occurs as a result of skin exposure remove contaminated clothing and wash clothing before next use. If symptoms persist seek medical advice.

Ingestion (Swallowing): If material is accidentally swallowed do not induce vomiting and seek medical advice.

Inhalation: Move the patient to fresh air. If the patient is unconscious, place in the recovery position and seek medical attention immediately.

This information should be taken with the patient when seeking medical advice
Do not give victim anything to drink if he/she is unconscious





Product Name: **Polyglaze**
Reviewed Date: **January 2010**

Health & Safety Data Sheet Reference: **FT107**

5- FIRE FIGHTING MEASURES

Use dry powder extinguishers only.
Fire fighters must have self-contained breathing apparatus.

6- ACCIDENTAL RELEASE MEASURES

Spillages must be contained with an inert, non-combustible material and prevented from entering surface drains. Dispose of according to Local Regulations.
Remove all sources of ignition.
Do not allow spillages to enter surface waters or basements where flammable vapours may form an explosive atmosphere

7- HANDLING AND STORAGE

Store away from sources of heat and ignition.
The product must be protected from freezing.
When handling avoid contact with eyes and skin.
All chemical preparations should be stored securely where they cannot be interfered with or used by unauthorized persons.

8- EXPOSURE CONTROLS/PERSONAL PROTECTION

Prolonged exposure may cause irritation and/or dermatitis.
Suitable protection should be worn to prevent contact with eyes and skin.

Solvent	Occupational Exposure Limit
White Spirit	100ppm
HF aromatic	50ppm

Exposure controls:

Occupational exposure controls:

Respiratory protection: Provide sufficient ventilation during use to ensure Workplace exposure limit is not reached. Where workers encounter concentrations higher than the exposure limits, they must wear suitable, organic vapour approved masks,

- A1, A2, EN 141.

For short periods or an air-fed mask for longer exposure.

Hand protection: All types of protective gloves are suitable to protect the hands during use, product does not attack rubber, latex nitrile or other similar materials. Suitable work-wear or overalls should be used to protect clothing and skin.

Eye protection: Safety glasses/goggles with side shields or face shield should be used when handling this material to protect from liquid droplets or splashes.





Product Name: **Polyglaze**
Reviewed Date: **January 2010**

Health & Safety Data Sheet Reference: **FT107**

Keep away from foodstuffs, drinks and tobacco. Wash hands before breaks and at end of work. Keep working clothes separate. Immediately remove contaminated clothing.

Environmental exposure controls:

No specific environmental legislation applies, but good practice should be followed. The product should not be allowed to spill or run into surface waters.

9- PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear amber Liquid	Odour:	White spirit
Auto Ignition:	400°C	pH:	Not Applicable
Density:	SG 0.866 (average)	Boiling point/range:	150 - 200°C
Flash Point:	Above 32°C	Oxidising properties:	None
Solubility in Water:	Immiscible with water	Flammability:	Flammable
Viscosity:	40 Seconds (Ford cup 4)	Auto-flammability:	230°C

10- STABILITY AND REACTIVITY

This preparation is generally unreactive and stable when stored and handled correctly.

Conditions to avoid: Heat, sparks, flames and direct sunlight.

Materials to avoid: Strong oxidising agents, amines and alcohols.

Reacts with water to produce carbon dioxide, risk of bursting in closed containers due to the pressure build-up.

Hazardous decomposition products: If burnt may produce toxic fumes including carbon monoxide and various oxides of carbon and nitrogen.

11- TOXICOLOGICAL INFORMATION

May cause irritation to the eyes and skin.

Any person with a history of skin sensitisation must be careful when handling this product.

Moderately toxic but may cause irritation to the eyes and mucous membranes.

Vapour may cause drowsiness, nausea and dizziness.

12- ECOLOGICAL INFORMATION

Not classified as harmful to the environment at these levels of concentration.

No ecological effects are known but the solvents used are likely to be a marine pollutant.

13- DISPOSAL CONSIDERATIONS

Non-recoverable waste is subject to the Duty of Care Of Waste Regulations.

Any surplus or waste arising from the normal use of this preparation must be disposed of in accordance with the hazard waste regulation 2005 and is classified as 08 01 11.

Empty containers should be treated as if still containing flammable material, classification 15 01 10.





floorTECH

**Manufacturers of Floor Seals and Maintenance
Products for Wood, Concrete and Sports Hall Floors**

floorTECH products
Goods Yard, Derby Road, Belper
Derbyshire DE56 1UX
Telephone: 01773 828111
Fax: 01773 828333
Email: info@floortechproducts.co.uk
www.floortechproducts.co.uk

Product Name: **Polyglaze**
Reviewed Date: **January 2010**

Health & Safety Data Sheet Reference: **FT107**

14- TRANSPORT INFORMATION

UN number: 1263
IMDG Code Class: 3.3
Packing group: III
ADR: 3
Proper Shipping Name: PAINT or PAINT RELATED MATERIAL
This preparation is classified as a marine pollutant.

15- REGULATORY INFORMATION

Classified as FLAMMABLE, label must carry a Flame symbol with the words "flammable liquid" and the following Risk and Safety phrases:

R10 : Flammable liquid
R51/53 : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 : Harmful: may cause lung damage if swallowed.
S2 : Keep out of the reach of children.
S43 : In case of fire use dry powder/foam/CO2. Never use water.
S24/25 : Avoid contact with skin and eyes.
S61 : Avoid release into the environment. Refer to special instructions/Safety data sheet.
S62 : If swallowed do not induce vomiting. Seek medical advice immediately and show the container or label.

This substance is classified as hazardous to health under Regulation 2 of the C.O.S.H.H. Regulations. Any employer or self-employed person using this product must carry out an assessment of the risks to health caused by the use of this substance.

16- OTHER INFORMATION

No other safety information applicable to this product.

It is recommended that all persons using this product be suitably trained in the use of relevant personnel protective equipment.

We cannot accept liability for any misuse of this product.

No other safety information is applicable to the use of this preparation for its intended purpose. This data sheet was compiled using information from raw material manufacturers, The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (as amended), the Approved classification and labelling guide (fifth edition) for supply, the Approved Supply List (eighth edition), EH40/2005 and the Approved Carriage List (third edition).

